

Waterial no.			
Specification	154320	Revision date	16.6.2023
Version	2.00	Page	1 of 7

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	: IGL Coatings™ ecocoat shield
FUNCTION	: Hydro- & oleophobic and easy-clean agent surface modifier and gloss enhancer
COMPANY	: Ominent Sdn Bhd
ADDRESS	: No.7, Jalan Majistret U1/26, Hicom-Glenmarie Industrial Park, Seksyen U1, 40150 Shah Alam, Selangor.
PHONE	: +60355690980
EMAIL ADDRESS	: regulations@iglcoatings.com

# 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture	
Regulation (EC) No. 1272/2008	
Physical hazards	
Flammable liquid	Category 3
Health hazards	
Skin irritation	Category 2
Serious eye damage	Category 1
Specific target organ toxicity – single exposure	Category 3
Aspiration Hazard	Category 1

#### 2.2 Label Elements

Regulation (EC) No. 1272/2008



Signal word

# Danger

# Hazard statements

- H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H318 Causes serious eye damage
- H336 May cause drowsiness or dizziness

# **Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P261 Avoid breathing dust/fume/gas/vapours.
- P264 Wash exposed skin thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
- present and easy to do. Continue rinsing.
- P331 Do NOT induce vomiting.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.



sion <b>2.00</b> Page 2 of 7
------------------------------

P370+P378	In case of fire: Use water spray, dry chemical or carbon dioxide to extinguish.
P403+P235	Store in well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to comply with local, state and federal regulations.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS No	Chemical Name			Quantity
	EC No	Index No	REACH No	
	Classification accord	ding to Regulation (EC) No. 1	272/2008 (CLP)	
64742-47-8	Distillates (petroleu	m), hydrotreated light		>70%
	265-149-8	Not applicable	Not applicable	
	Flam. Liq. 4; H227: A	Asp. Tox. 1: H304		
123-86-4	Butyl acetate			5-15%
	204-658-1	607-025-00-1	01-2119485493-29-0000	
	STOT SE 3: H336; Flam. Liq. 3: H226			
475645-84-2	Organopolysilazane			3-5%
	Not applicable	Not applicable	Not applicable	
	Acute Tox. 4: H302; Flam. Liq. 2: H225; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1: H317			
63148-61-8	Organopolysiloxane			0.1-1%
	814-597-8	Not applicable	Not applicable	
	Not applicable			
7782-42-5	Graphene		0.1-0.3%	
	231-955-3	Not applicable	01-2119486977-12-0000	
	Not applicable			

# 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General Information**

Take off contaminated clothing.

#### After Inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After skin contact

Gently wash with plenty of soap and water. In case of skin irritation, seek medical treatment.

#### After contact with eyes

Rinse cautiously with water at least 15 minutes. Remove contact lenses, if presence and easy to do In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Rinse mouth thoroughly with water. Do not induce vomiting. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

In all cases of doubt, or when symptoms persist, seek medical advice.

#### **4.2. Most important symptoms and effects, both acute and delayed** In all cases of doubt, or when symptoms persist, seek medical advice.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Material no. Specification

Version

**154320** F **2.00** F

Revision date Page



() igl coatings

# 5.1 Suitable extinguishing media

Water fog, dry chemical or carbon dioxide.

# 5.2 Unsuitable extinguishing media

High volume water jet.

# 5.3 Special hazards arising from the substance or mixture

Hazardous toxic and irritating fumes or smoke may be emitted

Vapours may travel considerable distance to ignition source and flash back.

Hazardous Combustion Products: Incomplete combustion products, Oxides of carbon, Smoke, Fume

# 5.4 Advise for firefighters

As in any fire, wear self-contained positive-pressure breathing apparatus, (MSHA/NIOSH approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

# 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition

Beware of vapours accumulating to form explosive concentrations. Vapour can accumulate in low areas. Wear personal protection equipment (refer to section 8).

#### **6.2. Environmental precautions**

Discharge into the environment must be avoided.

# 6.3. Methods and material for containment and cleaning up

Take up mechanically.

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated articles and floor according to the environmental legislation.

# 6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

# 7. HANDLING AND STORAGE

# 7.1. Precautions for safe handling

# Advice on safe handling

Do not breath vapour/dust. Avoid contact with eyes. Wash thoroughly with water and soap after handling. **Advice on protection against fire and explosion** 

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge

# Further information on handling

General protection and hygiene measures: refer to section 8.

# 7.2. Conditions for safe storage, including any incompatibilities

Further information on handling

# **Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

# Advice on storage compatibility

Do not store together with food and feeding stuffs.

#### Further information on storage conditions

Keep the packing dry and well-sealed to prevent contamination. Recommended storage temperature: 20C Protect against: UV-radiation/sunlight. heat.

Static electricity may accumulate and cause a fire hazard

# 7.3. Specific end use(s): refer to section 1.



Material no.			
Specification	154320	Revision date	16.6.2023
Version	2.00	Page	4 of 7

#### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

Component	Value type (Form of exposure)	Control parameter	Basis
	TWA	150 ppm 713 mg/m <sup>3</sup>	MY OEL
Butyl acetate	TWA	150 ppm	ACGIH
	STEL	200 ppm	ACGIH
Hydrotreated light distillates	RCP - TWA	1200 mg/m3 165 ppm	ExxonMobil

#### 8.2 Exposure Control

#### Advice on safe handling

#### 8.2.1 General protective and hygienic measures:

Wash hands before breaks and at the end of work. Ensure adequate ventilation.

#### 8.2.2 Personal protective equipment:

**Respiratory protection:** Required when aerosols are generated. Recommended filter type: ABEK filter **Protection of hands:** 

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of protective clothing should take into account all relevant work factors such as: other chemicals which may be handled, physical requirements, etc.

#### Material of gloves:

Butyl rubber.

#### Penetration time of glove material:

> 10 min

Eye protection: Tightly fitting eye goggles.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point	: 126 °C
Vapour Pressure	: 10.66 hPa (at 20°C)
Relative Vapor Density	: 4.0 (Air = 1)
Density	: 0.81 g/cm <b>3</b>
Melting Point	: Not applicable
Flash Point	: 58°C
рН	: No data available
Evaporation Rate	: Not applicable
Solubility in Water	: Not soluble
Appearance (colour)	: Transparent black
Appearance (form)	: Liquid
Odour	: Ester-like

#### **10. STABILITY AND REACTIVITY**

10.1 Reactivity: No further relevant information available.

10.2 Chemical stability: Stable under normal conditions.

Thermal decomposition / conditions to avoid: No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions**: No dangerous reaction known under conditions of normal use.

**10.4 Conditions to avoid**: Sunlight, heat, open flames, high temperature, sparks, static electrical charge, other ignition sources

10.5 Incompatible materials: Strong oxidizing agents.

**10.6 Hazardous decomposition products**: Possible decomposition products in case of hydrolysis: Hydrogen, ammonia, condensed siloxane.

Material no.



Specification	154320	Revision date	16.6.2023
Version	2.00	Page	5 of 7

# **11. TOXICOLOGICAL INFORMATION**

#### **11.1 Information on toxicological effects**

Exposure route	Endpoint	Value	Species
Oral	LD50	2858 mg/kg	Rat
Dermal	LD50	6041 mg/kg	Rabbit
Inhalation	LC50	2405 ppm	Rat

Skin corrosion/irritation: May causes mild skin irritation.

Eye irritation: May cause mild eye irritation.

Respiratory or skin sensitization: No information available.

**Summary of evaluation of the CMR properties:** Shall not be classified as a germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

**Specific target organ toxicity – single exposure**: Category 3. May cause drowsiness and dizziness.

#### Specific target organ toxicity – repeated exposure: No information available.

Aspiration hazard: May be fatal if swallowed and enters airways.

### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

#### Specified substance: Butyl acetate

Endpoint	Value	Species	Exposure time
LC50	18 mg/L	Fish (Pimephales promelas)	96 hours
EC50	44 mg/L	Water flea (Daphnia magna)	48 hours
ErC50	630 µg/L	Desmodesmus subspicatus (green algae)	72 hours

### Specified substance: Organopolysilazane

Endpoint	Value	Species	Exposure time
LC50	57.1 mg/L	Zebra fish (Danio rerio)	96 hours

#### Specified substance: Organopolysiloxane

Endpoint	Value	Species	Exposure time
LC50	>100 mg/L	Fish (Pimephales promelas)	96 hours
EC50	>10000 mg/L	Water flea (Daphnia magna)	48 hours

#### 12.2 Process of degradability

No data available.

- 12.3 Bioaccumulative potential
- No data available

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB Assessment

No data available.

# 12.6 Other adverse effects

Discharge into the environment must be avoided.

#### 13. DISPOSAL CONSIDERATION

#### 13.1 Waste treatment methods

Dispose of contents/container in accordance with local/regional/national/international regulation.

#### Sewage disposal-related information

Do not empty into drains.

#### **13.2 Relevant provisions relating to waste**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the



Material no.				
Specification	154320	Revision date	16.6.2023	
Version	2.00	Page	6 of 7	
Version	2.00	ruge	0 01 /	

industry and process.

#### **14. TRANSPORT INFORMATION**

14.1 IATA-DGR	
UN number	: 1263
UN proper shipping name	: Paint-related materials
Transport hazard class(es)	: 3
Packing group	: 111
Environmental hazards	: No
Special precautions for user	: -
Remarks	: -
14.2 IMDG-Code	
UN number	: 1263
UN proper shipping name	: Paint-related materials
Transport hazard class(es)	: 3
Packing group	: 111
Environmental hazards	: No
Marine pollutant	: No
EmS Code	:-

### **15. REGULATORY INFORMATION**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture US Federal Regulations

#### US. Toxic Substances Control Act (TSCA)

All chemical substances in this material are included on the TSCA Inventory of Chemical Substances.

# Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Hazardous Substance List

This product contains the following substance subject to the reporting requirements of CERCLA Hazardous Substance List

Component(s)	CAS No.	
Butyl acetate	123-86-4	

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Emergency Planning and Community Right-To-Know Act (EPCRA) Section 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

# Emergency Planning and Community Right-To-Know Act (EPCRA) Section 313 Toxics Release Inventory (TRI) Reporting

None present or none present in regulated quantities.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CRF 68.130)

None present or none present in regulated quantities.

#### **US. State Regulation**

**US. California Proposition 65** 

No ingredient requiring a warning under CA Prop 65.

#### **EU Regulation**

Material no.



Specification	154320	Revision date	16.6.2023
Version	2.00	Page	7 of 7

#### EU. Directive 2012/18/EU (SEVESO III) on Major Accident Hazards Involving Dangerous Substances, Annex I:

Not applicable.

#### **Korea Regulations**

KECI: All chemical substances in this material are included and in compliance with the KECI inventory. K-REACH: None present or none present in regulated quantities.

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **16. OTHER INFORMATION**

#### **Further information**

Changes since the last version are highlighted in the margin. This version replaces all previous versions. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material use in combination with any other materials or any process, unless specified in the test.