(in accordance with Regulation (EU) 2020/878)

Ecocoat Kenzo Top-



Version 3

Date of compilation: 7/10/2024

Page 1 of 10 Print date: 11/04/2025

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: UFI: Ecocoat Kenzo Top CXQU-39GJ-KTK9-WW4M

1.2 Relevant identified uses of the substance or mixture and uses advised against. Hydro & oleophobizing and easy clean agent surface modifier and gloss enhancer.

Uses advised against:

For professional use only.

1.3 Details of the supplier of the safety data sheet.

Company:	IGL Coatings
Address:	No. 7, Jalan Majistret U1/26, Hicom-Glenmarie Industrial Park, Seksyen U1
City:	40150 - Shah Alam
Province:	Selangor
Telephone:	+0355690980
E-mail:	regulations@iglcoatings.com
Web:	https://iglcoatings.com/

1.4 Emergency telephone number: (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

The product is not classified as hazardous within the meaning of Regulation (EC) No 1272/2008.

2.2 Label elements.

None.

2.3 Other hazards.

The mixture does not contain substances classified as PBT. The mixture does not contain substances classified as vPvB. The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

		(*)Classification - Regulation (EC) No 1272/2008		
Identifiers	Name	Concentrate	Classification	Specifics concentration limits and Acute toxicity estimate
CAS No: 63148-62-9	Dimethyl siloxane	50 - 75 %	-	-

(in accordance with Regulation (EU) 2020/878)

Ecocoat Kenzo Top-



Version 3

Date of compilation: 7/10/2024

Page 2 of 10 Print date: 11/04/2025

CAS No: 25265-71-8 EC No: 246-770-3	Dipropylene glycol	25 - 50 %	-	-
CAS No: 5593-70-4 EC No: 227-006-8	titanium tetrabutanolate	0 - 1 %	Eye Dam. 1, H318 - Flam. Liq. 3, H226 - STOT SE 3, H335 - STOT SE 3, H336 - Skin Irrit. 2, H315	-
CAS No: Proprietary	Proprietary	0 - 2.5 %	-	-
CAS No: 123-86-4 EC No: 204-658-1 Index No: 607-025-00-1	n-butyl acetate	0 - 20 %	Flam. Liq. 3, H226 - STOT SE 3, H336	-
CAS No: 7782-42-5 EC No: 231-955-3	Graphene	0 - 2.5 %	-	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[2] Substance with a national workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

Due to the composition and type of the substances present in the product, no particular warnings are necessary.

Inhalation.

If breathing stops, seek emergency medical attention. Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eve contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing.

Ingestion.

Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

(in accordance with Regulation (EU) 2020/878)

Ecocoat Kenzo Top-



Version 3

Date of compilation: 7/10/2024

Page 3 of 10 Print date: 11/04/2025

SECTION 5: FIREFIGHTING MEASURES.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, diatomaceous earth) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The product does not require special handling measures, the following general measures are recommended:

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

The product does not require special storage measures. As general storage measures, sources of heat, radiation, electricity and contact with food should be avoided.

Keep away from oxidising agents and from highly acidic or alkaline materials.

Store the containers between 5 and 35 ° C, in a dry and well-ventilated place.

Store according to local legislation. Observe indications on the label. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

(in accordance with Regulation (EU) 2020/878)

Ecocoat Kenzo Top-



Version 3

Date of compilation: 7/10/2024

Page 4 of 10 Print date: 11/04/2025

7.3 Specific end use(s).

Hydro & oleophobizing and easy clean agent surface modifier and gloss enhancer.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
Dipropylene glycol	DNEL	Inhalation, Chronic, Systemic effects	238
CAS No: 25265-71-8	(Workers)		(mg/m ³)
EC No: 246-770-3			
	DNEL	Inhalation, Chronic, Systemic effects	480
	(Workers)		(mg/m ³)
	DNEL	Inhalation, Chronic, Systemic effects	102,34
	(Consumers)		(mg/m ³)
	DNEL	Inhalation, Short term, Systemic effects	960
	(Workers)		(mg/m ³)
	DNEL	Inhalation, Short term, Systemic effects	859,7
	(Consumers)		(mg/m ³)
n-butyl acetate	DNEL	Inhalation, Chronic, Local effects	480
CAS No: 123-86-4	(Workers)		(mg/m ³)
EC No: 204-658-1	DNEL	Inhalation, Chronic, Local effects	102,34
2010301	(Consumers)		(mg/m ³)
	DNEL	Inhalation, Short term, Local effects	960
	(Workers)		(mg/m ³)
	DNEL	Inhalation, Short term, Local effects	859,7
	(Consumers)		(mg/m ³)
	DNEL	Oral, Chronic, Systemic effects	3,4 (mg/kg
	(Consumers)		bw/day)
	DNEL	Dermal, Chronic, Systemic effects	3,4 (mg/kg
	(Consumers)		bw/day)
Graphene	DNEL	Inhalation, Chronic, Local effects	1,2
CAS No: 7782-42-5	(Workers)		(mg/m ³)
EC No: 231-955-3			

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum. Concentration levels PNEC:

Name	Details	Value
	aqua (freshwater)	0,18 (mg/l)
	aqua (marine water)	0,018 (mg/l)
	aqua (intermittent releases)	0,36 (mg/l)
n-butyl acetate	STP	35,6 (mg/l)
CAS No: 123-86-4	sediment (freshwater)	0,981 (mg/kg
EC No: 204-658-1		sediment dw)
	sediment (marine water)	0,0981
		(mg/kg
		sediment dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

(in accordance with Regulation (EU) 2020/878)

Ecocoat Kenzo Top-



Version 3 Date of compilation: 7/10/2024 Page 5 of 10 Print date: 11/04/2025

8.2 Exposure controls. Measures of a technical nature:

Concentration:	100 %
Uses:	Hydro & oleophobizing and easy clean agent surface modifier and gloss enhancer.
Breathing protecti	on:
If the recommended	technical measures are observed, no individual protection equipment is necessary.
Hand protection:	
If the product is han	dled correctly, no individual protection equipment is necessary.
Eye protection:	
If the product is han	dled correctly, no individual protection equipment is necessary.
Skin protection:	
PPE:	Work footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN 20347
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should
Maintenance.	not be used by other people.
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any
	injury resulting from an accident

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid. Colour: Colourless. Odour: Peculiar. Odour threshold: Not available. Melting point: Not available. Freezing point: Not available. Boiling point or initial boiling point and boiling range: 180 - 220 °C Flammability: Not available. Lower explosion limit: Not available. Upper explosion limit: Not available. Flash point: 70 °C Auto-ignition temperature: Not available. Decomposition temperature: Not available. pH: Not available. Kinematic viscosity: Not available. Solubility: Not available. Hydrosolubility: Not available. Liposolubility: Not available. Partition coefficient n-octanol/water (log value): Not available. Vapour pressure: Not available. Absolute density: 994 kg/m3 Relative density: Not available. Relative vapour density: Not available. Particle characteristics: Not available.

9.2 Other information

Not available.

(in accordance with Regulation (EU) 2020/878)

Ecocoat Kenzo Top-



Version 3

Date of compilation: 7/10/2024

Page 6 of 10 Print date: 11/04/2025

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.

Toxicological information about the substances present in the composition.

Name		Acute toxicity			
		Туре	Test	Kind	Value
			LD50	Rat	10800 mg/kg bw [1]
		Oral		Toxicity Data. J , Part B. Vol. 1,	lournal of the American College of Pg. 196, 1992
n-butyl acetate			LD50	Rabbit	>17600 mg/kg bw [1]
		Dermal		aterial Data Har 1, Pg. 7, 1974	ndbook, Vol.1: Organic Solvents,
CAS No: 123-86-4	EC No: 204-658-1	Inhalation	LC50	Rat	1.85 mg/l/4 h [1]
CAS NO. 123-00-4	AS NO: 123-00-4 EC NO: 204-050-1		[1] Inhalat	ion Toxicology.	Vol. 9, Pg. 623, 1997

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

c) serious eye damage/irritation; Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation; Not conclusive data for classification.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

(in accordance with Regulation (EU) 2020/878)

Ecocoat Kenzo Top-



Version 3

Date of compilation: 7/10/2024

Page 7 of 10 Print date: 11/04/2025

h) STOT-single exposure; Based on available data, the classification criteria are not met.

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
Name	Туре	Test	Kind	Value
n-butyl acetate	Fish	LC50 Fish 81 mg/l (96 h) [1] [1] Wellens, H. 1982. Comparison of the Sensitivity of Brachydanio rerio and Leuciscus idus by Testing the Fish Toxicity of Chemicals and Wastewaters. Z.Wasser- Abwasser-Forsch. 51(2):49-52 (GER) (ENG ABS). Dawson, G.W., A.L. Jennings, D. Drozdowski, and E. Rider 1977. The Acute Toxicity of 47 Industrial Chemicals to Fresh and Saltwater Fishes. J.Hazard.Mater. 1(4):303-318 (OECDG Data File)		
	Aquatic invertebrates	EC50	Daphnia sp. tion, 1959	44 mg/l (48 h) [1]
	Aquatic plants	EC50	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	674.7 mg/l (72 h) [1]
CAS No: 123-86-4 EC No: 204-658-1		Umweltbur		n inhibition test, according to deral Environment Agency) y 1984)

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name			Bioac	cumulation	
	Name	Log Pow	BCF	NOECs	Level
Dipropylene glycol		-0,67	_	_	Verv low
CAS No: 25265-71-8	EC No: 246-770-3	-0,07	-	-	veryiow

(in accordance with Regulation (EU) 2020/878)

Ecocoat Kenzo Top-



Version 3

Date of compilation: 7/10/2024

Page 8 of 10 Print date: 11/04/2025

n-butyl acetate		1 70			Manakish
CAS No: 123-86-4	EC No: 204-658-1	1,78	-	-	Very high

12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number or ID number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description: ADR/RID: Not classified as hazardous for transport. IMDG: Not classified as hazardous for transport. ICAO/IATA: Not classified as hazardous for transport.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): Not applicable.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Maritime transport in bulk according to IMO instruments.

Not classified as hazardous for transport.

(in accordance with Regulation (EU) 2020/878)

Ecocoat Kenzo Top-



Version 3

Date of compilation: 7/10/2024

Page 9 of 10 Print date: 11/04/2025

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the	Conditions of restriction
Designation of the substance, of the group of substances or of the mixture 3. Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	 Shall not be used in: ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, tricks and jokes, games for one or more participants, or any article intended to be used as such, even with ornamental aspects, Articles not complying with paragraph 1 shall not be placed on the market. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: can be used as fuel in decorative oil lamps for supply to the general public, and, present an aspiration hazard and are labelled with H304,
	market, that the following requirements are met: (a) lamp oils, labelled with H304, intended for supply to the general public
	 (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life threatening lung damage'; (c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.

Kind of pollutant to water (Germany): WGK 1: Slightly hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

The supplier has carried out a Chemical Safety Assessment for the substance/mixture.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H318 Causes serious eye damage. H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

(in accordance with Regulation (EU) 2020/878)

Ecocoat Kenzo Top-



Version 3 Date of compilation: 7/10/2024

Page 10 of 10 Print date: 11/04/2025

Classification codes:

Eye Dam. 1 : Serious eye damage, Category 1 Flam. Liq. 3 : Flammable liquid, Category 3 STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3 Skin Irrit. 2 : Skin irritant, Category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]: Physical hazards On basis of test data Health hazards Calculation method Calculation method Environmental hazards

It is recommended that the product only be employed for the purposes advised.

Abbreviations and acronyms used:

- Facility Regulations for handling substances that are hazardous for the water. AwSV:
- BCF: Bioconcentration factor.
- European Committee for Standardization. CEN:
- Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be DMEL: considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- NOEC: No observed effect concentration.
- Predicted No Effect Concentration, concentration of the substance below which adverse effects are PNEC: not expected in the environmental compartment.
- WGK: Water hazard classes.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2020/878. Regulation (EC) No 1907/2006. Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.