(in accordance with Regulation (EU) 2020/878)

Marine Solutions Prep-



Version 3 Page 1 of 11
Date of compilation: 9/10/2024 Print date: 14/04/2025

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: Marine Solutions Prep UFI: Y3QU-19KK-HTKC-9G9Y

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Surface decontamination cleaner.

Uses advised against:

For professional use only.

1.3 Details of the supplier of the safety data sheet.

Company: IGL Coatings

Address: No. 7, Jalan Majistret U1/26, Hicom-Glenmarie Industrial Park, Seksyen U1

City: 40150 - Shah Alam Province: Selangor +0355690980

E-mail: regulations@iglcoatings.com Web: https://iglcoatings.com/

1.4 Emergency telephone number: (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008: Eye Irrit. 2: Causes serious eye irritation. Flam. Liq. 3: Flammable liquid and vapour. STOT SE 3: May cause drowsiness or dizziness.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:





Signal Word:

Warning

Hazard statements:

H226 Flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P370+P378 In case of fire: Use carbon dioxide, dry chemical powder, water spray, alcohol resistant foam to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container according to local, state and federal regulations.

(in accordance with Regulation (EU) 2020/878)

Marine Solutions Prep-



Version 3 Page 2 of 11
Date of compilation: 9/10/2024 Print date: 14/04/2025

2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

				(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	Specifics concentration limits and Acute toxicity estimate	
CAS No: 67-63-0 EC No: 200-661-7 Index No: 603-117-00-0	propan-2-ol, isopropyl alcohol, isopropanol	20 - 75 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-	
CAS No: 7732-18-5 EC No: 231-791-2	water	25 - 50 %	-	-	

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

Skin contact

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

^[2] Substance with a national workplace exposure limit (see section 8.1).

(in accordance with Regulation (EU) 2020/878)

Marine Solutions Prep-



Version 3 Page 3 of 11
Date of compilation: 9/10/2024 Print date: 14/04/2025

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

${\bf 5.2 \ Special \ hazards \ arising \ from \ the \ substance \ or \ mixture.}$

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, diatomaceous earth) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

(in accordance with Regulation (EU) 2020/878)

Marine Solutions Prep-



Version 3 Page 4 of 11
Date of compilation: 9/10/2024 Print date: 14/04/2025

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use antistatic footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Surface decontamination cleaner.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
	DNEL	Inhalation, Chronic, Systemic effects	500
	(Workers)		(mg/m³)
	DNEL	Inhalation, Chronic, Systemic effects	89
	(Consumers)		(mg/m³)
propan-2-ol, isopropyl alcohol, isopropanol	DNEL	Dermal, Chronic, Systemic effects	888
CAS No: 67-63-0	(Workers)		(mg/kg
EC No: 200-661-7			bw/day)
LC NO. 200-001-7	DNEL	Dermal, Chronic, Systemic effects	319
	(Consumers)		(mg/kg
			bw/day)
	DNEL	Oral, Chronic, Systemic effects	26 (mg/kg
	(Consumers)		bw/day)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
propan-2-ol, isopropyl alcohol, isopropanol	aqua (freshwater)	140,9 (mg/L)
CAS No: 67-63-0	aqua (marine water)	140,9 (mg/L)
EC No: 200-661-7	aqua (intermittent releases)	140,9 (mg/L)

(in accordance with Regulation (EU) 2020/878)





 Version 3
 Page 5 of 11

 Date of compilation: 9/10/2024
 Print date: 14/04/2025

sediment (freshwater)	552 (mg/kg
	sediment dw)
sediment (marine water)	552 (mg/kg
	sediment dw)
Soil	28 (mg/kg
	soil dw)
STP	2251 (mg/L)
oral (Hazard for predators)	160 (mg/kg
	food)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %			
Uses:	Surface decontamination cleaner.			
Breathing protection:				
If the recommended	technical measures are observed, no individual protection equipment is necessary.			
Hand protection:				
•	dled correctly, no individual protection equipment is necessary.			
Eye protection:				
PPE:	Face shield.			
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.			
CEN standards:	EN 165, EN 166, EN 167, EN 168			
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.			
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.			
Skin protection:				
PPE:	Anti-static protective clothing.			
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.			
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5			
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.			
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.			
PPE:	Anti-static safety footwear.			
Characteristics:	«CE» marking, category II.			
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346			
Maintenance: Observations:	The footwear should be checked regularly The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.			

(in accordance with Regulation (EU) 2020/878)

Marine Solutions Prep-



Version 3 Page 6 of 11
Date of compilation: 9/10/2024 Print date: 14/04/2025

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid. Colour: Yellow. Odour: Citrus.

Odour threshold: Not available. Melting point: Not available. Freezing point: Not available.

Boiling point or initial boiling point and boiling range: 85 °C

Flammability: Not available. Lower explosion limit: Not available. Upper explosion limit: Not available.

Flash point: 26 °C

Auto-ignition temperature: Not available. Decomposition temperature: Not available.

pH: 5.8 - 6.7

Kinematic viscosity: Not available.

Solubility: Soluble.

Hydrosolubility: Not available. Liposolubility: Not available.

Partition coefficient n-octanol/water (log value): Not available.

Vapour pressure: Not available. Absolute density: 880 kg/m3 Relative density: Not available. Relative vapour density: Not available. Particle characteristics: Not available.

9.2 Other information

Not available.

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

(in accordance with Regulation (EU) 2020/878)

Marine Solutions Prep-



Version 3 Page 7 of 11
Date of compilation: 9/10/2024 Print date: 14/04/2025

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information about the substances present in the composition.

Name		Acute toxicity				
		Туре	Test	Kind	Value	
propan-2-ol, isopropyl alcohol, isopropanol			LD50	Rat	5050 mg/kg bw [1]	
		Oral	[1] Gigiena i Sanitariya. For English translation, see HYSAAV. Vol. 43(1), Pg. 8, 1978			
			LD50	Rabbit	12800 mg/kg bw [1]	
		Dermal	[1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 100, 1974			
			LC50	Rat	>10000 ppm (6 h) [1]	
CAS No: 67-63-0	EC No: 200-661-7	Inhalation	[1] OECD (report, 199	,	Acute Inhalation Toxicity), study	

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3: May cause drowsiness or dizziness.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

(in accordance with Regulation (EU) 2020/878)

Marine Solutions Prep-



Version 3 Page 8 of 11
Date of compilation: 9/10/2024 Print date: 14/04/2025

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity				
Name	Туре	Test	Kind	Value	
	Fish	LC50 Fish 9640 mg/l (96 h) [1] [1] Brooke, L.T., D.J. Call, D.L. Geiger, and C.E. Northcott 1984. Acute Toxicities of Organic Chemicals to Fathead Minnows (Pimephales promelas), Vol. 1. Center for Lake Superior Environmental Stud., Univ.of Wisconsin-Superior,			
propan-2-ol, isopropyl alcohol, isopropanol	Aquatic invertebrates		Crustacean	1400 mg/l (48 h) [1] icity of Oil-Sinking Agents.	
		Toxicity threshold	Scenedesmus quadricauda	1800 mg/L (7 d) [1]	
CAS No: 67-63-0 EC No: 200-661-7	Aquatic plants	Pollutants t	on Inhibition Test, W	Thresholds of Water nd Protozoa in the Cell later Research Vol. 14. pp.	

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name		Bioaccumulation			
		Log Pow	BCF	NOECs	Level
propan-2-ol, isopropyl alcohol, isopropanol		0,05	_	_	High
CAS No: 67-63-0	EC No: 200-661-7	0,03	_	_	riigii

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

(in accordance with Regulation (EU) 2020/878)

Marine Solutions Prep-



Version 3 Page 9 of 11
Date of compilation: 9/10/2024 Print date: 14/04/2025

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

<u>Sea</u>: Transport by ship: IMDG. Transport documentation: Bill of lading <u>Air</u>: Transport by plane: ICAO/IATA. Transport document: Airway bill.

14.1 UN number or ID number.

UN No: UN1263

14.2 UN proper shipping name.

Description:

ADR/RID: UN 1263, PAINT RELATED MATERIAL, 3, PG III, (E) IMDG: UN 1263, PAINT RELATED MATERIAL, 3, PG III (26°C) ICAO/IATA: UN 1263, PAINT RELATED MATERIAL, 3, PG III

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: No

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E

14.6 Special precautions for user.

Labels: 3



Hazard number: Not applicable.

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Proceed in accordance with point 6. IMDG Code segregation group: 18 Alkalis ADR LQ: 5 L

IMDG LQ: 5 L ICAO LQ: 10 L

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

(in accordance with Regulation (EU) 2020/878)

Marine Solutions Prep-



Version 3 Page 10 of 11 Date of compilation: 9/10/2024 Print date: 14/04/2025

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the **Conditions of restriction** group of substances or of the mixture 3. Liquid substances or mixtures fulfilling 1. Shall not be used in: the criteria for any of the following hazard - ornamental articles intended to produce light or colour effects by means of classes or categories set out in Annex I to different phases, for example in ornamental lamps and ashtrays, Regulation (EC) No 1272/2008: - tricks and jokes, (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, - games for one or more participants, or any article intended to be used as 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; market. (b) hazard classes 3.1 to 3.6, 3.7 adverse 3. Shall not be placed on the market if they contain a colouring agent, effects on sexual function and fertility or on unless required for fiscal reasons, or perfume, or both, if they: development, 3.8 effects other than narcotic - can be used as fuel in decorative oil lamps for supply to the general public, effects, 3.9 and 3.10; and, (c) hazard class 4.1; - present an aspiration hazard and are labelled with H304, (d) hazard class 5.1. 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010, 'Just a sip of lamp oil - or even sucking the wick of lamps - may lead to life-threatening lung damage'; (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life threatening lung damage'; (c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.

Kind of pollutant to water (Germany): WGK 1: Slightly hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

The supplier has carried out a Chemical Safety Assessment for the substance/mixture.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

(in accordance with Regulation (EU) 2020/878)

Marine Solutions Prep-



 Version 3
 Page 11 of 11

 Date of compilation: 9/10/2024
 Print date: 14/04/2025

Classification codes:

Eye Irrit. 2 : Eye irritation, Category 2 Flam. Liq. 2 : Flammable liquid, Category 2 Flam. Liq. 3 : Flammable liquid, Category 3

STOT SE 3: Specific target organ toxicity following a single exposure, Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method Environmental hazards Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road. AwSV: Facility Regulations for handling substances that are hazardous for the water.

BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

EC50: Half maximal effective concentration.
 PPE: Personal protection equipment.
 IATA: International Air Transport Association.
 ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

NOEC: No observed effect concentration.

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are

not expected in the environmental compartment.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

WGK: Water hazard classes.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/ Regulation (EU) 2020/878. Regulation (EC) No 1907/2006. Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.